

CLAIMS

WHAT IS CLAIMED:

1 1. A built-in self-test controller including:
2 a memory built-in self-test engine capable of executing a memory built-in self-test;
3 and
4 a memory built-in self-test signature generated on execution of the memory built-in
5 self-test.

1 2. The built-in self-test controller of claim 1, wherein the memory built-in self-
2 test signature register includes the results of at least one paranoid check.

1 3. The built-in self-test controller of claim 1, wherein the memory built-in self-
2 test signature includes a bit indicating whether the memory built-in self-test is done.

1 4. The built-in self-test controller of claim 1, wherein the memory built-in self-
2 test engine comprises:
3 a memory built-in self-test state machine; and
4 a nested memory built-in self-test engine operating the memory built-in self-test state
5 machine.

1 5. The built-in self-test controller of claim 4, wherein the memory built-in self-
2 test state machine comprises:
3 a reset state entered upon receipt of an external reset signal;
4 an initiate state entered from the reset state upon receipt of at least one of a memory
5 built-in self-test run signal and a memory built-in self-test select signal;
6 a flush state entered from the initiate state upon the initialization of components and
7 signals in the memory built-in self-test domain in the initiate state;
8 a test state entered into from the flush state upon completing a flush of a plurality of
9 memory components to a known state; and
10 a done state entered into upon completing the test of each of the memory components
11 in the memory built-in self-test.

1 6. The built-in self-test controller of claim 1, wherein the memory built-in self-
2 test engine comprises:

3 a plurality of alternative memory built-in self-test state machines; and
4 a nested memory built-in self-test engine operating a predetermined one of the
5 memory built-in self-test state machines.

1 7. The built-in self-test controller of claim 6, wherein each of the memory built-
2 in self-test engines comprises:

3 a reset state entered upon receipt of an external reset signal;
4 an initiate state entered from the reset state upon receipt of at least one of a memory
5 built-in self-test run signal and a memory built-in self-test select signal;
6 a flush state entered from the initiate state upon the initialization of components and
7 signals in the memory built-in self-test domain in the initiate state;
8 a test state entered into from the flush state; and
9 a done state entered into upon completing the test of each of a plurality of memory
10 components in the memory built-in self-test.

11 8. The built-in self-test controller of claim 1, further comprising:
12 a logic built-in self-test engine capable of executing a logic built-in self-test and
1 storing the results thereof; and
2 a multiple input signature register capable of storing the results of an executed logic
3 built-in self-test.

4 9. A built-in self-test controller including:
5 means for executing a memory built-in self-test; and
6 means for storing the results generated on execution of the memory executing means.

7 10. The built-in self-test controller of claim 9, wherein the memory storing means
8 includes the results of at least one paranoid check.

9 11. The built-in self-test controller of claim 9, wherein the memory storing means
10 includes a bit indicating whether the memory built-in self-test is done.

11 12. The built-in self-test controller of claim 9, wherein the memory executing
12 means comprises:
1 a memory built-in self-test state machine; and
2 a nested memory built-in self-test engine operating the memory built-in self-test state
3 machine.
4
5

13. The built-in self-test controller of claim 9, wherein the memory executing means comprises:

a plurality of alternative memory built-in self-test state machines; and
a nested memory built-in self-test engine operating a predetermined one of the memory built-in self-test state machines.

14. The built-in self-test controller of claim 9, further comprising:
means for executing a logic built-in self-test and storing the results thereof; and
means for storing the results of an executed logic built-in self-test.

15. A integrated circuit device including:
a plurality of memory components;
a testing interface; and
a built-in self-test controller controlled through the testing interface, the built-in self-test controller including:
a memory built-in self-test engine capable of performing a memory built-in self-test; and
a memory built-in self-test signature generated upon an execution of the memory built-in self-test.

16. The integrated circuit device of claim 15, wherein the memory built-in self-test signature register is further capable of storing the results of at least one paranoid check.

17. The integrated circuit device of claim 15, wherein the memory built-in self-test signature register includes a bit indicating whether the memory built-in self-test is done.

18. The integrated circuit device of claim 15, wherein the memory built-in self-test engine comprises:
a memory built-in self-test state machine; and
a nested memory built-in self-test engine operating the memory built-in self-test state machine.

19. The integrated circuit device of claim 15, wherein the memory built-in self-test state machine comprises:
a reset state entered upon receipt of an external reset signal;

an initiate state entered from the reset state upon receipt of at least one of a memory built-in self-test run signal and a memory built-in self-test select signal;
a flush state entered from the initiate state upon the initialization of components and signals in the memory built-in self-test domain in the initiate state;
a test state entered into from the flush state; and
a done state entered into upon completing the test of each of a plurality of memory components in the memory built-in self-test.

20. The integrated circuit device of claim 15, wherein the memory built-in self-test engine comprises:

a plurality of alternative memory built-in self-test state machines; and
a nested memory built-in self-test engine operating a predetermined one of the memory built-in self-test state machines.

21. The integrated circuit device of claim 15, wherein the memory components include a static random access memory device.

22. The integrated circuit device of claim 15, wherein the testing interface comprises a Joint Test Action Group tap controller.

23. The integrated circuit device of claim 15, further comprising:
a logic built-in self-test engine capable of executing a logic built-in self-test and storing the results thereof; and
a multiple input signature register capable of storing the results of an executed logic built-in self-test.

24. A method for performing a memory built-in self-test, the method comprising:
externally resetting a memory built-in self-test engine and a memory built-in self-test signature;
generating the memory built-in self-test signature upon an execution of a memory built-in self-test by the memory built-in self-test engine; and
reading the generated memory built-in self-test signature.

25. The method of claim 24, wherein the execution of the memory built-in self-test includes:

3 initiating a plurality of components and signals in a memory built-in self-test engine
4 and the memory built-in self-test signature upon receipt of at least one of a
5 memory built-in self-test run signal and a memory built-in self-test select
6 signal;

7 flushing the contents of a plurality of memory components to a known state after
8 initialization of the components and the signals; and
9 testing the flushed memory components.

1 26. The method of claim 25, wherein generating the memory built-in self-test
2 signature includes:

3 storing the results of the testing in a memory built-in self-test signature register.

1 27. The method of claim 24, wherein generating the memory built-in self-test
2 signature includes storing the results of the testing in a memory built-in self-testing register.

1 28. The method of claim 24, wherein performing the memory built-in self-test
2 further includes at least one of:

3 performing at least one paranoid check; and

4 storing the results of the paranoid check in the memory built-in self-test signature
register.

1 29. The method of claim 24, wherein performing the memory built-in self-test
2 further includes setting a bit in the memory built-in self-test signature indicating whether the
3 memory built-in self-test is done.

1 30. The method of claim 24, wherein externally resetting the memory built-in self-
2 test engine includes externally resetting a memory built-in self-test engine including:

3 a memory built-in self-test state machine; and

4 a nested memory built-in self-test engine.

1 31. The method of claim 30, wherein externally resetting the memory built-in self-
2 test state machine includes externally resetting one of a plurality of memory built-in self-test
3 state machines.

1 32. The method of claim 30, wherein flushing the contents of the memory
2 components includes flushing the contents of a plurality of static random access memories.

1 33. A method for performing a built-in self-test on an integrated circuit device, the
2 method comprising:

3 interfacing the integrated circuit device with a tester;

4 performing a memory built-in self-test, including:

5 externally resetting a memory built-in self-test engine and a memory built-in
6 self-test signature;

7 generating the memory built-in self-test signature upon an execution of a
8 memory built-in self-test by the memory built-in self-test engine; and

9 reading the generated memory built-in self-test signature.

1 34. The method of claim 33, wherein the execution of the memory built-in self-
2 test includes:

3 initiating a plurality of components and signals in a memory built-in self-test
4 engine and the memory built-in self-test signature register upon receipt
5 of at least one of a memory built-in self-test run signal and a memory
6 built-in self-test select signal;

7 flushing the contents of a plurality of memory components to a known state
8 after initialization of the components and the signals in the memory
9 built-in self-test domain; and

10 testing the flushed memory components.

1 35. The method of claim 33, wherein generating the memory built-in self-test
2 signature includes storing the results in a memory built-in self-test signature register.

1 36. The method of claim 33, wherein performing the memory built-in self-test
2 further includes at least one of:

3 performing at least one paranoid check; and

4 storing the results of the paranoid check in the memory built-in self-test signature
5 register.

1 37. The method of claim 33, wherein performing the memory built-in self-test
2 further includes setting a bit in the memory built-in self-test signature indicating whether the
3 memory built-in self-test is done.

1 38. The method of claim 33, wherein externally resetting the memory built-in self-
2 test engine includes externally resetting a memory built-in self-test engine including:
3 a memory built-in self-test state machine; and
4 a nested memory built-in self-test engine.

1 39. The method of claim 33, further comprising:
2 performing a logic built-in self-test; and
3 reading the results of the logic built-in self-test.